

Face – UFace302

Multi-Biometric
Time Attendance
& Access Control System



Specification

- Face Capacity: 3,000
- Fingerprints Capacity: 4,000
- ID card Capacity: 10,000
- Transaction Capacity: 1, 00,000
- Push Data: Yes
- Communication: TCP/IP, RS232/485, USB Host
- Display: 4.3-Inch Touch Screen

Standard Functions:

- Automatic Status Switch, Self-Service Query, Work Code, SMS, DST, T9 Input, 9 Digit User ID, Scheduled Bell,
- Photo ID Access Control Interfaces for: 3rd Party
- Electric Lock, Door Sensor, Exit Button, Alarm /FR1200
- Weigand: Output

Optional Functions:

- MiFare 13.56 MHz, Wi-Fi, 3G, 2000 mAh Backup Battery, FR-1200
- Power Supply: 12V 3A
- Operating Temperature: 0°C~45 °C
- Operating Humidity: 20%-80%
- Dimension (in mm): 193.6 x 165.2 x 86
- Package Weight: 1.6 kg

Features :

- High verification speed
- Advanced and user-friendly UI
- Chip encryption for firmware protection
- Optional back up battery providing approximately 3+ hours of continuous operation
- Easy to extend functions and customize client's requirements
- One face template is registered for one user only
- Able to detect whether the face is an actual face or a photo, enhancing the security level of verification

Disclaimer : Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.