

F18

Standalone Fingerprint Time
Attendance & Access Control System



Specification

- Fingerprints Capacity: 3000
- Card Capacity: 5000
- Transaction Capacity: 100,000
- Biometric
- CPU: 32 bit High End Microprocessor
- Fingerprint sensor: 500 DPI Optical sensor
- FAR: <0.0001%
- FRR: <=1%
- Identification speed: <=0.5sec
- Algorithm Version: 9/10
- Audio & Visual
- Display: 2.8" color TFT
- Keypad: Yes
- LED Indicator: Green/Red
- Schedule Bell/Speaker: Mini Speaker
- Communication: TCP/IP, USB host
- Push data: Standard
- DLST, Self Service Query, Status Switch
- Power Supply: DC 12V-1.5A

- Operating Temp: 0°C-45 °C
- Operating Humidity: 20%-80%
- Dimensions (in mm): (L) 183 x (W) 80 x (H) 42
- Weigand: In & Out
- Relay: 12 V relay for lock EM lock, Bolt Lock or Strike lock
- Door Sensor: Yes
- Anti-Pass back: Yes
- Door Bell: Yes
- Support exit readers: FR 1200/KR 500
- Battery / GPRS: NO
- Mifare / HID Pox (Optional)
- WIFI (Optional)
- External Speaker output available (Optional)
- External Bulb output available (Optional)
- Support External Printer (Optional)
- EtimeTracklite desktop & web
- Web based Device Manager/ePush server using Push data, Helps developers & integrators
- Supports 3rd Party Payroll/HRMS/ERP and Other applications
- Time & Attendance, Canteen management, School attendance,
- Production Management, Gym & Clubs

Disclaimer : Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.