

## F22

Ultra-Thin Fingerprint  
TA with Access Control  
System with Inbuilt Wi Fi



### Specification

- Fingerprint Capacity: 3,000
- Card Capacity: 5,000
- Finger Algorithm: Finger VX10.0
- Record Capacity: 30,000
- CPU: 32 bit Microprocessor
- Core board: ZLM60
- Biometric
- Fingerprint sensor: 500 DPI Silk ID sensor
- FAR: 0.0001%
- FRR: 1%
- Identification speed: <0.5 sec
- Algorithm Version: 10
- Display: 2.8-inch TFT Screen
- Keypad: Yes
- LED Indicator: Green/Red
- Communication: RS232/485, TCP/IP, USB-host, Built in Wi-Fi
- Weigand: In & Out
- Push Data Yes (support both static IP and domain server)

- Standard Features: work code, SMS, DLST, Self-service query, Status Switch
- Standard Functions
- DST, Automatic Status Switch,
- Record query, T9 input, 14 digit user ID, Anti-pass back
- MI fare (Optional)
- Power Supply: DC 12V-1.5Amp
- Operating Temperature: 0°C-45°C
- Operating Humidity: 20%-80%
- Dimension (in mm): (L) 158.5 x (W) 78.0 x (H) 19.4mm

## Features

- 2.4inch TFT color screen and Touch keys
- Ultrathin and elegant design
- Full Access Control Features: Anti-pass back, access control interface for 3rd party electric lock, door sensor, exit button, alarm
- Standard Wi-Fi
- Network interface by TCP/IP or RS485
- Multiple Verification Modes: Multi-verification
- Methods (card is optional) providing user various choices
- Supports exit readers: FR 1200, Push Button, KR500, No-Touch and KR503E/M

Disclaimer : Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.